



Panel Printer PNP-64



PNP-64

SPECIFICATION FOR THE PNP-64 PANEL PRINTER

Printing Method	:	Direct Thermal Printing.
Print Width	:	48 mm
Print Speed	:	50mm per second
Resolution	:	203 DPI (8 dots/mm)
Paper Loading	:	Easy 'Clam Shell' type
Characters per line	:	29 (default) or 42
Character set	:	96 Characters ASCII (As shown below) : !"£\$%&' () * + , - . / 0 1 2 3 4 5 6 7 8 9 : ; < = > ? @ A B C D E F G H I J K L M N O P Q R S T U V W X Y Z [\] ^ _ ` a b c d e f g h i j k l m n o p q r s t u v w x y z ° # ~
Fonts	:	Normal, Double Width, Double Height & Quadruple Size
Sensors	:	'No Paper' sensor
Paper Type	:	Direct Thermal Paper
Paper Roll	:	Width 58mm. Outer Diameter 40mm
Reliability	:	MCBF 50 km
Interface	:	RS-232C
Data Buffer	:	768 Characters
Power	:	Logic 5VDC @ 250mA Mechanism 8.5 VDC @ 1.5A (Peak 3A)
Cutter	:	Manual
Dimensions	:	External 80(W) x 76(L) x 43(H) mm Panel Cut-out 76.2 x 72mm