


SMP-2000IIA



**3 Inch Impact Dot Printer Mechanism
with Autocutter**

The SMP-2000IIA boasts an auto cutter feature and duplicate and bi-direction high speed printing. High reliability and low operating costs make this model perfectly suited for fiscal and general ECR applications.

SPECIFICATION FOR THE SMP-2000IIA IMPACT MECHANISM

Print	Printing Speed	4.5LPS (3 inch)
	Printing Method	9-pin, Serial impact dot
	Printing Direction	Bi-direction
	Printing Width(mm)	45.3 (1.8"), 62.5 (2.5 inch)
Resolution(Dpi)	Horizontal	168dpi
	Vertical	144dpi Paper
	Media	Roll Paper
Paper	Width(mm)	57.5 ± 0.5mm, 76.2 ± 0.7mm
	Thickness	1 Sheet: 0.06~ 0.085mm Total : 0.2mm
Reliability	Mechanism	10,000,000 Lines
	TPH	300,000,000 dots/Wire
Power Supply	Mechanism	24V± 10%
	Logic	5V± 5%
	Font Size	Font A: 7 X 9 Font B: 9 X 9 Korean: 15 X 9 Chinese: 16 X 16
	Printing Columns	Font A: 42, 30 Font B: 35, 25 Korean: 24, 17 Chinese: 23 X 16
	Paper Feeding	Performed by Step motor
	Oper Temp	0 ~ 50 °C
	Weight(g)	746 (Except Ribbon Cassette)
	Dimensions (W*L*H)	127.8 X 100.3 X 72.8 mm
Option	Black Mark	Applicable
	Auto Cutter	Auto Cutter