## Thermal Panel Printer PNP-5850







Analytical



Petrol Dispensers



**Innovative** and **Sleek**Printer with USB!



## Thermal Panel Printer PNP-5850













Twin push locks help you remove and refit the printer easily during device servicing.



18 m long paper rolls ensure uninterrupted printing for long periods of time.



Irritation-free
printing
experience with
a super silent
printing mechanism



Quick plug & play connectivity boosts assembly speed & convenience



Additional USB port provided along with serial to keep the connectivity flexible.







Print method	Thermal line printing
Paper loading method	Easy paper loading
Paper width	58 mm
Print width	48 mm
Print speed	60 mm/sec
Life of printing head	50 km
Character size	12 x 24 • 24 x 24
Outline dimension	84.6 x 84.6 x 60 mm
Interface	RS232/USB
Input power	DC 5V-8.5V 2A
Operating temperature	5°C-50°C
Storage temperature	-10°C-50°C
Operating humidity	35%-85% RH
Storage humidity	10%-90% RH
Paper type	Thermal paper
Weight	Around 200 g
Printer dots	8 dots/mm
Sensors	Temperature and paper end sensor
Fonts	ANK, GB2312, customer defined language
Printing data	Support bmp bitmap barcode
Barcode types	EAN-13, EAN-8, CODE39, CODE128
Buffer	16K
Commands	ESC/POS
Thermal head	100 000 000 pulses

