



High Performance Easy Maintenance Ergonomic Design Enterprise Printer

3-Inch POS Printer

ENT Plus™



Key Features



Fast Printing : Up to 260 mm/s

The ENT Plus™ delivers a fast printing speed of up to 260 mm/s that suits any cash counter environment. With its 203 dpi resolution, clear and crisp text and graphic results are assured.



Ideal For Compact Enterprise Counters

ENT Plus™ features highest in class speed of 260 mm/s, 15% faster than comparable models. Status indicators, high MCBF life combined with speed, supercharges a high load, high volume and compact receipt/ticket counter.



Triple Interface : USB + Serial + LAN

The ENT Plus™ offers a fast printing speed of up to 260 mm/s and a triple interface options that fit customers' business needs.

General Features

- Dense Built: Create Strong MPoS Setups in 35% Lesser Space.
- Unparalleled Data Processing: Print Receipts upto 500 items in One shot.
- Supreme Durability: Accept upto 3000 receipts Per Day Consistently for 5+ Years.
- Cyclonic Speed: Process Customer Queues 32% Faster Consistently.
- Smart Status Detection: Professional Triple LED Status Display.
- Driverless Printing (Optional): Implement Seamless Cloud Printing Systems
- Supercharged Kiosk: Straight Entry into Any Ticketing Kiosk (For Kiosk Manufacturers)



ENT Plus™

3-Inch POS Printer

Specifications

Printing

Printing Method

Direct Thermal Line Printing

Resolution

Standard 203 dpi (8 dots / mm)
Emulated 180 dpi (7 dots / mm)

Print Speed

Max. 260 mm / s

Print Width

80 mm

Interface

Standard

USB + Serial + Ethernet

Optional

Bluetooth or Wi-Fi

Page Mode

Support

Memory

Ram

4 MB

Flash

4 MB

Fonts

Alphanumeric

ASCII 9 x 17, 12 x 24 dots

User-defined

YES

Codepage

Optional international character sets: PC437(std.Europe), Katakana, PC850(Multilingual), PC860(Portuguese), PC863(Canadian), PC865(Nordic), PC857(Turkish), PC737(Greek), ISO08859-7(Greek), WPC1252, PC866(Cyrillic #2), PC852(Latin 2), PC858(Euro), KU42(Thai), TIS11(Thai), TIS18(Thai), PC720(Arabic), WPC775(Baltic Rim), PC855(Cyrillic), PC862(Hebrew), PC864(Arabic), ISO8859-2(Latin2), ISO8859-15(Latin9), WPC1250(Latin 2), WPC1251(Cyrillic), WPC1253(Greek),

WPC1254(Turkish), WPC1255(Hebrew), WPC1256(Arabic), WPC1257(Baltic Rim), WPC1258(Vietnamese), MIK(Cyrillic), PC755(Latin 2), Iran, Iran II, Latvian, ISO-8859-1(WestEur), ISO-8859-3(Latin 3), ISO-8859-4(Baltic), ISO-8859-5(Cyrillic), ISO-8859-6(Arabic), ISO-8859-8(Hebrew), ISO-8859-9(Turkish), PC856, PC3848(ABICOMP), MONGOLIAN, VISCII

Barcode

1D

UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93

2D

PDF417, QR Code

Graphics

Support bitmap printing with different density and user defined bitmap printing. (Max. size of each bitmap is 64k, the total size of bitmap is 256k)

Detection

Standard

Paper out sensor, cover open sensor

Optional

Paper near end sensor

LED Indicator

Power

Blue LED

Paper

Orange LED

Error

Red LED

Reliability

TPH life

150 km

Cutter life

2 million cuts

Power Supply

Input

AC 100V-240V

Output

DC 24V / 2.5A

Paper

Paper Type

Thermal Receipt Paper

Paper Width

58 mm / 80 mm

Paper Thickness

0.056~0.1 mm

Roll Paper Diameter

Max. OD Ø83 mm

Paper Load

Front or Top paper loading

Paper Cut

Partial cut or full cut

Environment

Operation

0°C~45°C, 25%~85%RH

Storage

-30°C~60°C, 5%~95%RH

Physical Characteristics

Dimension

134.8(L)x132(W)x132(H)mm

Weight

1.37 KG (Without paper roll)

Options & Accessories

USB/Serial Cable, Paper Roll, Power Adapter, Power Cord, CD, Quick Start Guide

Software

Emulation

ESC/POS

Driver

Windows 2000 / XP / Win7 / Win8 / Win10 / POS Ready / Linux / OPOS /

SDK

WinCE, Win Mobile, Android, iOS



Maxim Peripherals Pvt. Ltd.

106, Pradhan Bldg., Aarey Road (Near Subway), Goregaon (East), Mumbai 400063, India.
Mobile : +91-9372573685, +91-9326108275, Email : sales@xvc-india.in

www.xvc-india.in